



Trans-Cling™ II Low Tack Vinyl

DESCRIPTION:

A vinyl film with a low-tack pressure sensitive adhesive for use on smooth surfaces. It is available in white matte and a clear gloss surface.

CHARACTERISTICS:

- Can be applied to most clean, non-porous surfaces.
- Withstands many weather conditions.
- Temperature ranges from -40°F to 180°F.

APPLICATIONS:

- Interior and exterior doorway signs.
- Refrigerator/freezer point-of-purchase signs.
- Point-of-purchase decals for appliances.
- Window decals for stores and cars...and more.

TECHNICAL DATA:

PROPERTIES	CLEAR POLISHED	WHITE MATTE
THICKNESS - tolerance is ± 5% or .001 whichever is greatest	4.8 to 5.2 mil with adhesive.	
PRINTING	Material suitable for screen process, offset lithography, and flexography.	
DIMENSIONAL STABILITY	GOOD	
MIN. APPLICATION TEMPERATURE	+50°F	
EXTERIOR EXPOSURE	Test for U.V. discolor under extreme conditions.	
ADHESION	Glass - 6 to 16 oz./in. Removable up to 1 year on interior applications and 6 months on exterior applications.	
WATER & HUMIDITY RESISTANCE	Fair. Slight haze will develop in high humidity conditions and will clear when normal humidity returns. Immersion not recommended.	
SHELF LIFE	2 years when stored at 74° F and 50% relative humidity.	

NOTE: All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. Transilwrap shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

