



Trans-Stick™ High Tack Vinyl

DESCRIPTION:

Trans-Stick™, a Transilwrap Trans-Cling™ product, is a removable, high-tack, pressure sensitive white vinyl on a 90# liner. It is available top coated and non-top coated in 20"x 27" and 27"x 38" sheets and 54"x 750' rolls for sheeting.

CHARACTERISTICS:

- Trans-Stick™ is excellent for indoor and outdoor use, especially transit advertising applications.
- Excellent for bumper stickers, temporary P-O-P decals, and product markings.
- Can be printed using conventional or UV inks for flexo, offset, or screen process printing.
- It can be removed from surfaces, without residue, for up to 6 months. Applied parts will last longer but may not remove cleanly after 6 months. *(test adhesion to glass, as adhesion may increase with time)*
- Good dimensional stability and two year shelf life under proper storage conditions.

TECHNICAL DATA:

PROPERTIES	TYPICAL VALUES	TEST METHOD
THICKNESS	3.4 mil film; 4.2 - 4.6 mils with adhesive	
APPLICATION TEMPERATURE	+ 40° F	
SERVICE TEMPERATURE	-40° F to +200° F	
SURFACE FINISH	Gloss	
ADHESION	Minimum 24 oz./in.	PSTC method #1
WATER RESISTANCE	Not recommended where immersed.	
HUMIDITY RESISTANCE	Fair	
SOLVENT RESISTANCE	Good: Edge sealing is recommended for best results against solvent penetration	
STORAGE STABILITY	2 YR. @ 70° F and 50% relative humidity	

Note: The stated values are typical data and are not specification of guarantee. Transilwrap suggests that purchaser confirm product compatibility prior to use of this product. Stated values are believed to be accurate, but all information is presented without guarantee or responsibility on the part of Transilwrap Company, Inc.

