

Product Data Sheet

DIGI-Jet UV PRO-Print® Synthetic Paper

Description:

DIGI-Jet UV PRO-Print is an extruded, mineral filled polypropylene. It is available in white opaque with a matte/matte finish in 54" rolls. This product is specially treated with our proprietary UV coating for optimum printing results.

Characteristics:

- Superior ink receptivity.
- Can be folded, hot stamped, riveted, stapled and sewn.
- Environmentally friendly.
- High heat resistance.

Applications:

- Retractable displays.
- Inexpensive indoor banners.
- Posters.
- Trade show display panels.

Technical Data

Properties	
Thickness	15 and 20-mil
Tensile Strength (machine direction)	(15mil) 3000 PSI
Tensile Strength (cross direction)	(15mil) 2400 PSI
Initiated Tear Resistance (machine direction)	1 lb
Initiated Tear Resistance (Cross direction)	4 lbs
Stiffness @ 15mil (machine direction)	34 Taber Units
Stiffness @ 15mil (cross direction)	44 Taber Units
Compatibility	Most large format UV printers
Shelf Life	6 months when stored at 74° F and 50% relative humidity

Note: All information, recommendations and suggestions contained herein, including without limitations, stated values (collectively the "information") shall only be used as a guide by purchaser and not for any other purpose. The information does not constitute a warranty nor guarantee of any type whatsoever. Purchaser should independently determine suitability of all materials purchased and must confirm adaptability and other characteristics by conducting its own tests. Transilwrap shall have no liability as a result of any loss, expense, damage, cost or other injury which results from purchaser's reliance on the information

Printed in the USA 8/2007

