



Trans-Banner™ I Polyolefin

DESCRIPTION:

Trans Banner I is a polyolefin film designed for printing banners and pennants. It is a minimal shrink film, excellent for three and four color printing, which allows for good registration. Trans Banner I is available in no and low slip formulations.

CHARACTERISTICS:

- Superior ink receptivity.
- High puncture and tear strength
- Excellent for display and P.O.P. applications.
- Can be guillotine cut, die cut, and punched.
- Excellent dimensional stability.

TECHNICAL DATA:

PROPERTIES		TYPICAL VALUES	TEST METHOD
THICKNESS - mils		7.5 mils	
YIELD - in ² /lb		27,506	
TENSILE STRENGTH - psi	MD	3,500	ASTM D-882
	TD	2,400	
ELONGATION - %	MD	1,000	
	TD	600	
SECANT MODULUS - psi	MD	90,000	
	TD	95,000	
TEAR STRENGTH - grams	MD	675	ASTM D-1922
	TD	1,800	
DART DROP - grams		325	ASTM D-1709
GLOSS - 45°		20.0	ASTM D-2457

NOTE: All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. Transilwrap shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

