



Trans-Kote® Digicore Laminating Film

DESCRIPTION:

Trans-Kote® Digicore Laminating Film is a premium grade PPG Teslin® base film with a superior polyethylene, proprietary thermal adhesive with 2 mils polyester backing.

CHARACTERISTICS:

- Water, oil, acid, and alkali resistant.
- Can be die cut.

TECHNICAL DATA

PROPERTIES		10/1/2 Teslin	ASTM
FINISH		MATTE	
THICKNESS ± 10%		.013	
SURFACE TENSION - dyne - adhesive side		48-56	
COEFFICIENT OF FRICTION OF BASE FILM SIDE		n/a	D 1894
TENSILE STRENGTH - psi ± 10%	MD	1,800	D 882
	TD	900	D 882
ELONGATION - %	MD	650	D 882
	TD	600	D 882
YIELD - in ² /lb.		4,010	
LAMINATING TEMPERATURE RANGE - °F - INTERNAL		240-270 °F	
BOND STRENGTH – lb/in – laminated to itself		8-10	

NOTE: All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. Transilwrap shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 05/12/2009

