



DIGIKote® Display White Opaque Laminating Film

DESCRIPTION:

DIGIKote® Display White Opaque is a rigid, low melt, thermally activated, white opaque laminating film that has been specially produced for pop-up and display applications that require no back light influence for large format graphics.

CHARACTERISTICS:

- Low-melt-point adhesive.
- Offers 100% dead white opacity.
- Gives wide format printers the option to produce two-sided images without light transference.
- Water, oil, acid, and alkali resistant.
- Can be die cut.

Slit Widths Available:

5 & 10 mil: 38", 43", 51", 55", 62"

Lengths Available:

5 & 10 mil: 38" thru 55" – 250'

5 mil: 62" – 250'

10 mil: 62" – 200'

TECHNICAL DATA:

PROPERTIES				ASTM
THICKNESS ± 10%		.005"	.010"	
SURFACE TENSION - dyne - adhesive side		48 to 52		
COEFFICIENT OF FRICTION OF BASE FILM SIDE		0.225		D 1894
TENSILE STRENGTH - psi + 10%	MD	8,400	7,600	D 882
	TD	11,200	10,900	
ELONGATION - %	MD	80	175	
	TD	70	110	
YIELD - in ² /lb		4,850	2,440	
LAMINATING TEMPERATURE RANGE - °F - internal		185° to 195°		
BOND STRENGTH - p/l - laminated to itself		21	28	

NOTE: All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. Transilwrap shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 10/18/2006

